

Pegler Valve

Chromium plated straight pattern brass service valve, copper x copper


808 Ball valve

808 Ball valve



General Information

| Size | Pattern No. | Pack 1 Qty | Pack 2 Qty | Code | Barcode | Price (£) each ex VAT |
|--------|----------------|---------------|---------------|-----------------|--------------|--------------------------|
| 15mm 8 | 808 | 10 | 80 | <u>523007</u> 5 | 013866017018 | £15.14 |
| 22mm 8 | 808 | 10 | 0 | <u>523008</u> 5 | 013866017025 | £30.51 |



Dimensions

| Code | Description | A B Kg |
|------------|--------------------------------|---------|
| 523007 15M | M 808 CP BRASS SERVICE VALVE C | XC 59 0 |
| 523008 22M | M 808 CP BRASS SERVICE VALVE C | XC 70 0 |

Pegler Yorkshire reserve the right to change specifications

Pressure and Temperature

| Description | Minimum Operating Pressure (bar) | Maximum Cold Working Pressure (bar) | Maximum Hot Working Pressure (bar) |
|-------------|-------------------------------------|-------------------------------------------|------------------------------------------|
| | No Minimum Operating Pressure | 16.0 bar at temperatures up to 30oC | 5.0 bar at temperatures up to 120oC |

Care and Maintenance

Care

No regular aesthetic care is required for this product

Maintenance

No regular maintenance is required for this product.

For any further help please contact the Service Support Team on: 0800 1560050.

Regulations

Regulations

It is important to ensure that the water supplies to your fitting are connected in accordance with the water regulations (WRAS) requirements and good plumbing practice.

This product has been designed in accordance with BS6675 standard.

The servicing valve should be fitted as close to the terminal fitting it is isolating, to avoid waste and misuse.