


Prestex

Gunmetal draincock, type A to BS 2879/2, male taper thread to BS 21



General Information

S	Size	Pattern No.	Pack 1 Qty	Pack 2 Qty	Code	Barcode	Price (£) each ex VAT
1	/2"	833 GM	20	0	<u>542027</u>	5013866017315	£31.95
3	3/4"	833 GM	1	10	542028	5022050560667	£62.95
1	"	833GM	1	5	542029	5022050560834	£188.39



Dimensions

Description	A B Kg
GUNMETAL TYPE A DRAINCO	OCK 55 0
	73 0
	79 1

Pegler Yorkshire reserve the right to change specifications

Pressure and Temperature

Description	Minimum Operating Pressure (bar)	Maximum Cold Working Pressure (bar)	Maximum Hot Working Pressure (bar)
	No Minimum Operating Pressure	20.0 bar at temperatures up to 120oC	Not Suitable for Maximum Hot Working Pressure

Care and Maintenance

Care

No regular aesthetic care is required for this product

Maintenance

No regular maintenance is required for this product.

For any further help please contact the Service Support Team on: 0800 1560050.

Regulations

Regulations

It is important to ensure that the water supplies to your shower are connected in accordance with the water regulations (WRAS) requirements and good plumbing practice.

This product has been designed in accordance with BS2879 and Kitemark standard.

Size Pattern No. Code PED Categorisation

1/2" 833 GM 542027 SEP 3/4" 833 GM 542028 SEP

Size Pattern No. Code PED Categorisation

1" 833GM 542029 SEP

Pegler Yorkshire reserve the right to change specifications

Materials

Component	Material
Body	Gunmetal
Headwork	Brass
Spindle	Brass
Washer	EPDM
Spindle 'O' ring	EPDM
Cap 'O' ring	EPDM
LS cover	Brass

Technical Suitability

Steam Water Oil Air Gas Inert Gas Combustible† Gas Corrosive†† Gas Oxygen

no yes yes no no no no no

Pegler Yorkshire reserve the right to change specifications

Gas application guide

Class 1. INERT Air, argon, carbon dioxide, helium, nitrogen

Class 2. COMBUSTIBLE Hydrogen, methane, natural gas, town gas

Class 3. CORROSIVE Chlorine, sulphur dioxide Class 4. OXYGEN

Class 1. INERT Air, argon, carbon dioxide, helium, nitrogen

† Valves are suitable for British Gas Applications Family Gases 1, 2 and 3.

†† Suitable in applications where moisture is completely absent.

Pegler Yorkshire Group Ltd, St Catherine's Ave, Doncaster, S Yorkshire, DN4 8DF
Telephone: Phone +44 (0) 844 243 4400 Fax: +44 (0) 844 243 9870 Website: www.pegleryorkshire.co.uk
Registered office: Pegler Yorkshire Group Ltd, St Catherine's Ave. Doncaster, S Yorkshire, DN4 8DF Company no: 00401507