

Endex

Backplate elbow, copper x BSP parallel female thread. Backplate with three hole fixing


N15 Elbow



General Information

| Size | Pattern No. | Pack 1 Qty | Pack 2 Qty | Code | Barcode | Price (£) each ex VAT |
|-------------|-------------|------------|------------|-----------------------|---------------|-----------------------|
| 15mm x 1/2" | N15 | 10 | 120 | 88555 | 5022050885555 | £2847.03 per 100 |
| 22mm x 3/4" | N15 | 10 | 80 | 88559 | 5022050885593 | £5401.64 per 100 |

N15 Elbow



Dimensions

| Code | Description | a | c | d | Za |
|-------|-----------------|----|----|----|----|
| 88555 | 15 x 1/2" N15 | 23 | 41 | 40 | 12 |
| 88559 | 22mm x 3/4" N15 | 31 | 27 | 49 | 15 |

Pegler Yorkshire reserve the right to change specifications

Guarantee

Pegler 25 Year Guarantee - Terms and Conditions

Products are subject to a 25 year guarantee that is between Pegler and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.


The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

Pressure and Temperature


| Size | -40°C (Min) | 30°C | 65°C | 110°C (Max) |
|-------------|-------------|-------|-------|-------------|
| 6mm to 28mm | 25bar | 25bar | 25bar | 16bar |

| Size | -40°C (Min) | 30°C | 65°C | 110°C (Max) |
|--------------|-------------|-------|-------|-------------|
| 35mm to 54mm | 25bar | 25bar | 16bar | 10bar |
| 67mm | 16bar | 16bar | 16bar | 10bar |


| Size | -15°C (Min) | 30°C | 65°C | 110°C (Max) |
|-------------|-------------|-------|-------|-------------|
| 6mm to 54mm | 16bar | 16bar | 10bar | 6bar |
| 67mm | 10bar | 10bar | 6bar | 4bar |



Pressure Loss Tables: Copper Water



Pressure Loss Tables: Copper Compressed Air



Pressure Loss Tables: Copper Gas

Care and Maintenance

Care

No regular aesthetic care is required for this product

Maintenance

No regular maintenance is required for this product.

For any further help please contact the Service Support Team on: 0800 1560050.