

Pegler Valve

Bronze swing type check valve. XPress union end x XPress end for copper/carbon steel/stainless steel tube

PSU 1060A Check valve



General Information

Size	Pattern No.	Pack 1 Qty	Pack 2 Qty	Code	Barcode	Price (£) each ex VAT
15mm	PSU1060A	1	10	122310	5022050559142	£65.60
22mm	PSU1060A	1	5	122312	5022050559166	£75.86
28mm	PSU1060A	1	5	122313	5022050559180	£114.76
35mm	PSU1060A	1	2	122314	5022050189066	£154.07
42mm	PSU1060A	1	0	122315	5022050559203	£199.72
54mm	PSU1060A	1	0	122316	5022050559227	£307.75

PSU 1060A Check valve

Dimensions

Code	Description	A	B
122310	15mm PSU1060A	131	45 0.557
122312	22mm PSU1060A	155	55 0.837
122313	28mm PSU1060A	164	60 1.214
122314	35mm PSU1060A	177	65 1.739
122315	42mm PSU1060A	200	75 2.169
122316	54mm PSU1060A	234	90 3.503

Pegler Yorkshire reserve the right to change specifications

Flow Rate

Size	Pattern No.	Code	Flow l/s	Kv	m3/h
15mm	PSU1060A	122310	0.04	1.80	
			0.10	3.70	
			0.20	5.10	
			0.40	5.70	
22mm	PSU1060A	122312	0.04	2.70	
			0.10	5.50	
			0.40	13.60	
			1.00	15.30	
28mm	PSU1060A	122313	0.01	7.70	
			0.20	13.90	
			0.30	18.40	
			1.00	25.30	
35mm	PSU1060A	122314	0.20	15.00	
			0.30	26.60	
			0.40	25.30	
			1.00	32.60	
42mm	PSU1060A	122315	0.40	30.30	
			0.60	40.20	
			0.80	48.50	
			3.00	54.40	
54mm	PSU1060A	122316	0.60	42.00	
			0.80	54.00	
			1.50	86.20	
			4.00	98.00	

Pressure and Temperature

Description	Minimum Operating Pressure (bar)	Maximum Cold Working Pressure (bar)	Maximum Hot Working Pressure (bar)
PSU 1060A Swing Check Valve	No minimum operating pressure.	16 bar up to 100oC	16 bar up to 100oC