

Pegler Valve

Ballofix isolating ball valve - straight pattern. Tectite push-fit ends for copper tube, CP DZR



General Information

Size	Pattern No.	Pack 1 Qty	Pack 2 Qty	Code	Barcode	Price (£) each ex VAT
15mm	6381ZA	1	5	<u>13073</u> 5	70853732604	8 £46.85

Screwdriver slot push-fit ball valve

Dimensions

Code Description A

13073 DN15 85 0.14

Pegler Yorkshire reserve the right to change specifications

Materials

Component	Material				
Body	DZR brass, chrome plated				
Ball	DZR brass, nickel plated				
'O' rings	EPDM				
Handle	Nylon PA6.6 (30% glass reinforced)				
Compression nut	Forged brass, chrome plated				
Compression cone Brass					

Technical Suitability

Steam	Water	Oil Air	Gas Inert	Gas Combustible†	Gas Corrosive††	Gas Oxygen			
no	yes	no no	no	no	no	no			
Pegler Yorkshire reserve the right to change specifications									

Gas application guide

Class 1. INERT Air, argon, carbon dioxide, helium, nitrogen

Class 2. COMBUSTIBLE Hydrogen, methane, natural gas, town gas

Class 3. CORROSIVE Chlorine, sulphur dioxide Class 4. OXYGEN

Class 1. INERT Air, argon, carbon dioxide, helium, nitrogen

† Valves are suitable for British Gas Applications Family Gases 1, 2 and 3.

†† Suitable in applications where moisture is completely absent.