


# Pegler Valve

Ductile iron butterfly valve. Semi lugged, to BS EN 593:2004, face to face dimensions to BS EN 558:2008



# **General Information**

Size	Pattern No.	Pack 1 Qty	Pack 2 Qty	Code	Barcode	Price (£) each ex VAT
DN65	V906	1	0	<u>15316</u>	5022050555366	£126.86
DN80	V906	1	0	<u>15317</u>	5022050555373	£153.17
DN100	V906	1	0	<u>15318</u>	5022050555380	£222.30
DN125	V906	1	0	<u>15319</u>	5022050555397	£313.88
DN150	V906	1	0	<u>15320</u>	5022050555403	£346.82
DN200	V906	1	0	<u>15321</u>	5022050555410	£823.16
						_



#### **Dimensions**

## Code Description A B C D

15316 DN65 V906 46 70 181 200 4.40 15317 DN80 V906 46 89 187 200 5.00 15318 DN100 V906 52 106 211 290 6.10 15319 DN125 V906 56 120 226 290 8.00 15320 DN150 V906 56 132 239 290 9.60 15321 DN200 V906 60 164 293 450 15.10

Pegler Yorkshire reserve the right to change specifications

#### **Flow Rate**

Size	Pattern No	. Code	Kv m3/h
DN65	V906	15316	229.32
DN80	V906	15317	353.34
DN100	V906	15318	702.00
DN125	V906	15319	1195.74
DN150	V906	15320	1847.43
DN200	V906	15321	3669.12

Pegler Yorkshire reserve the right to change specifications

#### **Guarantee**

Pegler 5 Year Guarantee - Terms and Conditions

Products are subject to a 5 year guarantee that is between Pegler and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble–free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

## **Materials**

Component	Material
Body	Ductile iron
Shaft	Stainless steel
Disc	Stainless steel
Bushes uo to 100mm	PTFE
Bushes uo to 125mm	Gunmetal
'O' ring	EPDM
Liner	EPDM

#### **Flange Data**

Size	Code	Flange Diameter (mm)	Pitch Circle Diameter (mm)	No of Bolts	Bolt Diameter (mm)	Hole Diameter (mm)	Raised Face Diameter (mm)	Raised Face Height (mm)	Thicki of Fla (mr	nge
DN65	15316	185	145	4 (2)	M16	19	-	-	20	
DN80	15317	200	160	8	M16	19	-	-	22	
DN100	15318	220	180	8	M16	19	-	-	24	
DN125	15319	250	210	8	M16	19	-	-	26	
DN150	15320	285	240	8	M20	23	-	-	26	
DN200	15321	340	295	12	M20	23	-	-	30	

Pegler Yorkshire reserve the right to change specifications

# **Technical Suitability**

Steam	Water	Oil Ai	r Gas Iner	t Gas Combustible	Gas Corrosive††	· Gas Oxygen		
no	yes	no no	no	no	no	no		
Pegler Vorkshire reserve the right to change specifications								

# Gas application guide

Class 1. INERT Air, argon, carbon dioxide, helium, nitrogen

Class 2. COMBUSTIBLE Hydrogen, methane, natural gas, town gas

Class 3. CORROSIVE Chlorine, sulphur dioxide Class 4. OXYGEN

Class 1. INERT Air, argon, carbon dioxide, helium, nitrogen

† Valves are suitable for British Gas Applications Family Gases 1, 2 and 3.

†† Suitable in applications where moisture is completely absent.