



Total protection against electro-magnetic corrosion using magnesium anode



Outer regulation of temperature



Led control



Security release valve



Installation Kit



Component Standard ROHS



Armoured copper heating element





Insulation Polyurethane



Safety thermostat

Model	H	L	P	
A12 SP	mm 410	mm 350	mm 220	over sink
A12 ST	mm 410	mm 350	mm 220	under sink
A15 SP	mm 400	mm 350	mm 260	over sink
A15 ST	mm 400	mm 350	mm 260	under sink



MODELS	Power Watts	Volts	Max Pressure bar	Heating Time $\Delta T = 50^{\circ}C$	Class Insul.	Humidity protection	Packaging mm
A12 SP	1500	230	8	30'	I	IPX4	470x390x250
A12 ST	1500	230	8	30'	I	IPX4	470x390x250
A15 SP	1500	230	8	32'	I	IPX4	470x400x290
A15 ST	1500	230	8	32'	I	IPX4	470x400x290

Model	Code N°	Bar code	description
2 YEARS GUARANTEE			
A12 SP	SE0012R2P	8023945 021222	Lt. 12 over sink
A12 ST	SE0012R2T	8023945 031221	Lt. 12 under sink
A15 SP	SE0015R2P	8023945 041220	Lt. 15 over sink
A15 ST	SE0015R2T	8023945 051229	Lt. 15 under sink
A15 SP TR	SE0015R2P001	8023945 151226	Lt. 15 over sink Ext. Regulation
A15 ST TR	SE0015R2T001	8023945 161226	Lt. 15 under sink Ext. Regulation
3 YEARS GUARANTEE			
A12 SP	SE0012R5P	8023945 021253	Lt. 12 over sink
A12 ST	SE0012R5T	8023945 031252	Lt. 12 under sink
A15 SP	SE0015R5P	8023945 041251	Lt. 15 over sink
A15 ST	SE0015R5T	8023945 051250	Lt. 15 under sink
A15 SP TR	SE0015R5P001	8023945 151257	Lt. 15 over sink Ext. Regulation
A15 ST TR	SE0015R5T001	8023945 161256	Lt. 15 under sink Ext. Regulation