



Component Standard
ROHS



Total protection against
electro-magnetic
corrosion
using magnesium anode



Armoured copper
heating element



Inspection flange
on 5 years range



Safety thermostat



Insulation
Polyurethane



Led control



Outer
regulation of
temperature

Model	A	B	C	F	G	I	L
SE 20	mm 350	360	100	70	250	65	120
SE 30	mm 450	360	100	70	250	65	120
SE 50	mm 510	460	100	130	350	130	150
SE 80	mm 700	460	100	130	350	130	150
SE 100	mm 805	460	100	160	350	130	150
SE 120	mm 1000	460	100	170	350	130	150
SE 150	mm 935	550	140	180	350	130	150
SE 200	mm 1105	550	140	180	350	130	150

MODELS	Power Watts	Volts	Max Pressure bar	Heating Time $\Delta T = 50^{\circ}C$	Class Insul.	Humidity protection	Packaging mm
SE 20	1200	230	8	64'	I	IPX4	410x410x460
SE 30	1200	230	8	89'	I	IPX4	410x410x550
SE 50	1200	230	8	170'	I	IPX4	590x480x500
SE 80	1200	230	8	260'	I	IPX4	775x480x500
SE 100	1500	230	8	245'	I	IPX4	920x480x500
SE 120	1500	230	8	315'	I	IPX4	1100x480x500
SE 150	2000	230	8	416'	I	IPX4	1060x570x570
SE 200	2000	230	8	500'	I	IPX4	1260x570x570

Model	Code N°	Bar code	description
2 YEARS GUARANTEE			
SE20	SE0020C2V	8023945 110322	Lt. 20 vertical electric
SE30	SE0030C2V	8023945 120321	Lt. 30 vertical electric
SE50	SE0050C2V	8023945 200320	Lt. 50 vertical electric
SE80	SE0080C2V	8023945 300327	Lt. 80 vertical electric
SE100	SE0100C2V	8023945 401222	Lt. 100 vertical electric
SE120	SE0120C2V	8023945 461230	Lt. 120 vertical electric
SE150	SE0150C2V	8023945 502127	Lt. 150 vertical electric
SE200	SE0200C2V	8023945 562121	Lt. 200 vertical electric
3 YEARS GUARANTEE			
SE20	SE0020C5V	8023945 110353	Lt. 20 vertical electric
SE30	SE0030C5V	8023945 120352	Lt. 30 vertical electric
SE50	SE0050C5V	8023945 200351	Lt. 50 vertical electric
SE80	SE0080C5V	8023945 300358	Lt. 80 vertical electric
SE100	SE0100C5V	8023945 401253	Lt. 100 vertical electric
SE120	SE0120C5V	8023945 461257	Lt. 120 vertical electric
SE150	SE0150C5V	8023945 502158	Lt. 150 vertical electric
SE200	SE0200C5V	8023945 562152	Lt. 200 vertical electric