



- According to 8061 & 8062 and QCS 2014

Nominal diameter (mm)	Class 1		Class 2		Class 3		Class 4	
	4 BAR		6 BAR		10 BAR		16 BAR	
	Wall thick (mm)	Weight kg/m	Wall thick (mm)	Weight kg/m	Wall thick (mm)	Weight kg/m	Wall thick (mm)	Weight kg/m
20	----	----	----	----	----	----	1.50	0.137
25	----	----	----	----	1.50	0.174	1.90	0.212
32	----	----	----	----	1.80	0.264	2.40	0.342
40	----	----	1.80	0.334	1.90	0.350	3.00	0.525
50	----	----	1.80	0.422	2.40	0.552	3.70	0.809
63	----	----	1.90	0.562	3.00	0.854	4.70	1.290
75	1.80	0.642	2.20	0.782	3.60	1.220	5.60	1.820
90	1.80	0.774	2.70	1.130	4.30	1.750	6.70	2.610
110	2.20	1.160	3.20	1.640	5.30	2.160	8.20	3.900
125	2.50	1.480	3.70	2.130	6.00	3.340	9.30	5.010
140	2.80	1.840	4.10	2.650	6.70	4.180	10.40	6.270
160	3.20	2.410	4.70	3.440	7.70	5.470	11.90	8.170
180	3.60	3.020	5.30	4.370	8.70	6.880	13.40	10.40
200	4.00	3.700	5.90	5.370	9.60	8.510	14.90	12.80
225	5.50	4.700	6.60	6.760	10.80	10.80	16.70	16.10
250	4.50	5.650	7.30	8.310	11.90	13.200	18.60	19.90

- Standard: DIN 8061/8062
- Length: 6 meters or 5.80 meters
- Color: grey or dark grey
- Socket: solvent or rubber ring sell