

Yorkshire

Straight union adaptor, copper x BSP taper female thread


68GHD Adaptor



General Information

Size	Pattern No.	Pack 1 Qty	Pack 2 Qty	Code	Barcode	Price (£) each ex VAT
8mm x 3/8"	68GHD	10	160	56536	5022050565365	£26.10
12mm x 1/2"	68GHD	10	150	56538	5022050565389	£28.69
15mm x 3/4"	68GHD	10	120	56539	5022050565396	£28.69
22mm x 1"	68GHD	5	60	56541	5022050565419	£38.83
28mm x 1.1/4"	68GHD	1	20	56542	5022050591432	£53.24
35mm x 1.1/2"	68GHD	1	15	56543	5022050591449	£96.52

68GHD Adaptor



Dimensions

Code	Description	a	Za	S
56536	8mm x 3/8" 68GHD	23	15	22
56538	12mm x 1/2" 68GHD	30	22	27
56539	15mm x 3/4" 68GHD	31	24	32
56541	22mm x 1" 68GHD	36	26	41
56542	28mm x 1 1/4" 68GHD	39	28	48
56543	35mm x 1 1/2" 68GHD	43	29	55

Pegler Yorkshire reserve the right to change specifications

Guarantee

Pegler 25 Year Guarantee - Terms and Conditions

Products are subject to a 25 year guarantee that is between Pegler and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

Pressure and Temperature

Size **-196°C (Min) 150°C 175°C 200°C (Max)**

Size	-196°C (Min)	150°C	175°C	200°C (Max)
6mm	242 bar	242 bar	151 bar	61 bar
8mm	202 bar	202 bar	128 bar	51 bar
10mm to 12mm	158 bar	158 bar	99 bar	40 bar
15mm to 54mm	69 bar	69 bar	43 bar	17 bar

Care and Maintenance

Care

No regular aesthetic care is required for this product

Maintenance

No regular maintenance is required for this product.

For any further help please contact the Service Support Team on: 0800 1560050.