

Yorkshire

Straight male union connector, copper x BSP taper male thread. Round-nose to cone joint


69GHD Connector



General Information

Size	Pattern No.	Pack 1 Qty	Pack 2 Qty	Code	Barcode	Price (£) each ex VAT
8mm x 1/4"	69GHD	10	80	56558	5022050565587	£41.22
12mm x 3/8"	69GHD	5	60	56560	5022050565600	£43.55
15mm x 1/2"	69GHD	5	60	56561	5022050565617	£50.76
22mm x 3/4"	69GHD	5	40	56563	5022050565631	£68.15
28mm x 1"	69GHD	1	20	56564	5022050591456	£151.96
35mm x 1 1/4"	69GHD	1	15	56565	5022050591463	£200.99
42mm x 1 1/2"	69GHD	1	10	56566	5022050591470	£241.45

69GHD Connector



Dimensions

Code	Description	a	Za	S	S1
56558	8mm x 1/4" 69GHD	44	37	22	19
56560	12mm x 3/8" 69GHD	54	46	27	22
56561	15mm x 1/2" 69GHD	59	52	32	27
56563	22mm x 3/4" 69GHD	69	60	41	36
56564	28mm x 1" 69GHD	76	65	48	46
56565	35mm x 1 1/4" 69GHD	87	74	55	50
56566	42mm x 1 1/2" 69GHD	93	78	66	60

Pegler Yorkshire reserve the right to change specifications

Guarantee

Pegler 25 Year Guarantee - Terms and Conditions

Products are subject to a 25 year guarantee that is between Pegler and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

Pressure and Temperature

Size	-196°C (Min)	150°C	175°C	200°C (Max)
6mm	242 bar	242 bar	151 bar	61 bar
8mm	202 bar	202 bar	128 bar	51 bar
10mm to 12mm	158 bar	158 bar	99 bar	40 bar
15mm to 54mm	69 bar	69 bar	43 bar	17 bar

Care and Maintenance

Care

No regular aesthetic care is required for this product

Maintenance

No regular maintenance is required for this product.

For any further help please contact the Service Support Team on: 0800 1560050.