

Yorkshire

Male hexagon nipple. BSP union thread x BSP taper male thread 60° cone


70GHD Nipple



General Information

Size	Pattern No.	Pack 1 Qty	Pack 2 Qty	Code	Barcode	Price (£) each ex VAT
1/2" x 3/8"	70GHD	10	240	56598	5022050565983	£15.02
3/4" x 1/2"	70GHD	5	140	56599	5022050565990	£21.96
1" x 3/4"	70GHD	5	100	56600	5022050566003	£29.28
1 1/4" x 1"	70GHD	1	30	56601	5022050591500	£104.45

70GHD Nipple



Dimensions

Code	Description	a	Za	S
56598	1/2" x 3/8" 70GHD	31	19	22
56599	3/4" x 1/2" 70GHD	35	20	27
56600	1" x 3/4" 70GHD	42	27	37
56601	1 1/4" x 1" 70GHD	46	27	46

Pegler Yorkshire reserve the right to change specifications

Guarantee

Pegler 25 Year Guarantee - Terms and Conditions

Products are subject to a 25 year guarantee that is between Pegler and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

Pressure and Temperature

Size	-196°C (Min)	150°C	175°C	200°C (Max)
6mm	242 bar	242 bar	151 bar	61 bar
8mm	202 bar	202 bar	128 bar	51 bar
10mm to 12mm	158 bar	158 bar	99 bar	40 bar

Size	-196°C (Min)	150°C	175°C	200°C (Max)
15mm to 54mm	69 bar	69 bar	43 bar	17 bar

Care and Maintenance

Care

No regular aesthetic care is required for this product

Maintenance

No regular maintenance is required for this product.

For any further help please contact the Service Support Team on: 0800 1560050.