



- According to B.S 3505 / 3506

Nominal diameter (inch)	Outside diameter (mm)		Class C 9 bar		Class D 12 bar		Class E 15 bar	
	Min.	Max.	Thick (mm)	Weight kg/m	Thick (mm)	Weight kg/m	Thick (mm)	Weight kg/m
1/2	21.20	21.50	-----	-----	-----	-----	1.70	0.158
3/4	26.60	26.90	-----	-----	-----	-----	1.90	0.225
1	33.40	33.70	-----	-----	-----	-----	2.20	0.350
1 1/4	42.10	42.40	-----	-----	2.20	0.434	2.70	0.508
1 1/2	48.10	48.40	-----	-----	2.50	0.534	3.10	0.668
2	60.20	60.50	2.50	0.683	3.10	0.850	3.90	1.042
3	88.10	89.10	3.50	1.417	4.60	1.834	5.70	2.250
4	114.10	114.50	4.50	2.350	6.00	3.050	7.30	3.700
6	168.00	168.50	6.60	5.084	8.80	6.720	10.80	8.134
8	218.80	219.40	7.80	7.860	10.30	10.170	12.60	12.280

- Color: grey or dark grey
- Length: 6 meters or 5.80 meters
- Socket: solvent or plain ends - end

- According to ASTM D 2241

Nominal diameter (inch)	Outside diameter (mm)		SDR 32.5		SDR 26		SDR 21	
			8.6 BAR 125 psi		11 BAR 160 psi		13.8 BAR 200 psi	
	Min.	Max.	Thick (mm)	Weight kg/m	Thick (mm)	Weight kg/m	Thick (mm)	Weight kg/m
1/2	21.20	21.50	-----	-----	-----	-----	-----	-----
3/4	26.60	26.90	-----	-----	-----	-----	-----	-----
1	33.40	33.70	-----	-----	-----	-----	-----	-----
1 1/4	42.10	42.40	-----	-----	-----	-----	-----	-----
1 1/2	48.10	48.40	1.50	-----	1.90	-----	2.30	0.520
2	60.20	60.50	1.90	0.558	2.30	0.657	2.90	0.804
3	88.10	89.10	2.70	1.130	3.40	1.390	4.20	1.680
4	114.10	114.50	3.50	1.850	4.40	2.280	5.40	2.790
6	168.00	168.50	5.20	3.990	6.50	4.970	8.00	6.060
8	218.80	219.40	6.70	6.720	8.40	8.350	10.40	10.20

- Color: white
- Length: 5.8 & 6 meter
- Socket plain: solvent cement weld (SC/J) or rubber ring seal
- Application: pressure pipe